

# Spectra PowerBox 3000C-Series

## Technical Data



### Features

- Pre-defined Box-PC
- Intel® Core™ i5-9500TE CPU
- 3 x mPCIe
- 2 x USB 3.2 Gen 2, 4 x USB 3.2 Gen 1, 2 x USB 2.0
- 2 x GLAN, 2 x COM, 2 x DP, 1 x DVI-I
- Windows® 10 IoT Enterprise

Model	Spectra PowerBox 30C Advanced 2	Spectra PowerBox 30C Advanced 2 Wide Temp
Article n°	167209	167210

### System Configuration

CPU	Intel® Core™ i5-9500TE 6 Cores / 6 Threads / Base Freq. 2.20 GHz / Burst Freq. 3.60 GHz	
RAM	8 GB	8 GB WT
SSD	256 GB 2.5" SATA-6G	256 GB 2.5" SATA-6G WT
Operating System	Microsoft® Windows® 10 IoT Enterprise 2021 LTSC, 64-bit, german / english	
Operating Temperature	0°C ~ +45°C	-40°C ~ +70°C

### Controllers & Interfaces

Ethernet	1 x Intel® i210 Gigabit-LAN, 1 x Intel® i219 Gigabit-LAN	
Graphics	integrated in CPU	
Audio	Realtek ALC888-GR	
Front IOs	2 x USB 3.2 Gen 2 1 x DP (4096 x 2304 4K)	
Rear IOs	4 x USB 3.2 Gen 1, 2 x USB 2.0 2 x RJ45 2 x RS-232/422/485 1 x DP (4096 x 2304 4K), 1 x DVI-I (1920 x 1200 FHD) 1 x Line-out, 1 x Mic-in, 1 x PS/2	


### Drives & Expansions

Free Storage Slots	1 x 2,5" SATA HDD/SSD (Hot-Swap, RAID 0/1 Support), 1 x PCIe4 NVMe Key M 2280 M.2, 3 x mSATA (mPCIe Slot), 2 x SIM	
PCI/PCIe Slots	-	
mPCIe Slots	3 x Full-Size for WiFi / GSM or expansion cards	
Antenna Holes	2 x for wireless communication	


### Further Data

Power	AT/ATX 9~48 V DC	
Dimensions (W x H x D)	227 x 88 x 261 mm	
Weight (net/gross)	5,1 kg / 7,5 kg	
Mounting	Wall	
Warranty	24 months	
Packing List	1 x Power Terminal Block (female), 1 x Remote Power Terminal Block, 1 x Fan Terminal Block, 1 x Driver/Manual Medium, 1 x Microsoft® Windows® Recovery Medium, 2 x rails for Wall mount, 1 x DVI to VGA Adapter	

# Spectra PowerBox 3000C-Series Interfaces



## Details Service lid



## Further options - Ask us!

### Interfaces for the proprietary slot

- 4 x Gigabit-LAN, RJ45
- 4 x Gigabit-LAN, M12
- 4 x Gigabit-LAN, XM12
- DIO (8-in / 8-out)
- 4 x RS-232/422/485
- 4 x RS-232/422/485, isolated
- 2 x Gigabit-LAN
- 2 x RS-232
- 2 x USB 3.2 Gen 1

### Further functions


- Power ignition
- PoE

### Power supply

Power adapter, 120W, 24V/5A, C14, 3-pin, Tube

### Mounting Kits

VESA Holder



All brand, company and product names are registered or otherwise protected works of their respective companies / owners. We reserve the right to change specifications and product description at any time without prior notice (March 2022)